

# Marking Punch



**CAUTION** Please wear proper safety gear while working.

## 11409SQ

- Chrome vanadium alloy steel
- Hardened and tempered control HRC60 for safe use
- Invert number 6 to be number 9 (For 11409SQ)
- The letter A~Z with extra "&" (ampersand) included (For 11427SQ)



• The position hole help to fix the marking punch



11409SQ

## 11427SQ



11427SQ

| KT NO.    | Font size |       | Contents         | Shank mm <sup>2</sup> | L mm | Kg   | Box / Carton |
|-----------|-----------|-------|------------------|-----------------------|------|------|--------------|
|           | mm        | inch  |                  |                       |      |      |              |
| 11409SQ02 | 2.0       | 5/64" | 9 PCS<br>0~9     | 6.35                  | 61   | 0.18 | 1 / 120      |
| 11409SQ03 | 3.0       | 1/8"  |                  | 6.35                  | 61   | 0.18 | 1 / 120      |
| 11409SQ04 | 4.0       | 5/32" |                  | 6.35                  | 59   | 0.18 | 1 / 120      |
| 11409SQ05 | 5.0       | 3/16" |                  | 8                     | 61   | 0.28 | 1 / 80       |
| 11409SQ06 | 6.0       | 1/4"  |                  | 9.53                  | 61   | 0.43 | 1 / 60       |
| 11409SQ08 | 8.0       | 5/16" |                  | 12.7                  | 71   | 0.78 | 1 / 30       |
| 11427SQ02 | 2.0       | 5/64" | 27 PCS<br>A~Z, & | 6.35                  | 61   | 0.52 | 1 / 50       |
| 11427SQ03 | 3.0       | 1/8"  |                  | 6.35                  | 61   | 0.52 | 1 / 50       |
| 11427SQ04 | 4.0       | 5/32" |                  | 6.35                  | 59   | 0.52 | 1 / 50       |
| 11427SQ05 | 5.0       | 3/16" |                  | 8                     | 61   | 0.82 | 1 / 30       |
| 11427SQ06 | 6.0       | 1/4"  |                  | 9.53                  | 61   | 1.25 | 1 / 20       |
| 11427SQ08 | 8.0       | 5/16" |                  | 12.7                  | 71   | 2.33 | 1 / 10       |

# Heavy Duty Marking Punch

## 11509SQ

- Chrome vanadium alloy steel
- Hardened and tempered control HRC60 for safe use
- Hardness reduced at striking end HRC40 to have longer life time
- Invert number 6 to be number 9 (For 11509SQ)
- The letter A~Z with extra "&" (ampersand) included (For 11527SQ)



11509SQ05

## 11527SQ



11527SQ05

| KT NO.    | Font size |       | Contents         | Shank mm <sup>2</sup> | L mm | Kg   | Box / Carton |
|-----------|-----------|-------|------------------|-----------------------|------|------|--------------|
|           | mm        | inch  |                  |                       |      |      |              |
| 11509SQ05 | 5.0       | 3/16" | 9 PCS<br>0~9     | 11                    | 61   | 0.56 | 1 / 30       |
| 11527SQ05 | 5.0       | 3/16" | 27 PCS<br>A~Z, & | 11                    | 61   | 1.70 | 1 / 10       |

