


T-type Deep Socket Wrench

115HM


- Shank material - chrome vanadium alloy steel
- Shank finishing - chrome plated
- Grip material - PP



KT NO.	mm	mm	L mm	g	kg
115H05M-10	5	260	300	127	12 / 96
115H06M-10	6	260	300	147	12 / 96
115H07M-10	7	260	300	162	12 / 96
115H08M-10	8	260	300	158	12 / 96
115H09M-10	9	260	300	161	12 / 96
115H10M-10	10	260	300	170	12 / 96
115H11M-10	11	260	300	203	12 / 96
115H12M-10	12	260	300	205	12 / 96
115H13M-10	13	260	300	205	12 / 96
115H08M-14	8	350	394	212	10 / 60
115H10M-14	10	350	394	221	10 / 60
115H13M-14	13	350	394	233	8 / 32

1184M

- T-shaped deep socket wrench
- Chrome vanadium alloy steel
- DIN 475




KT NO.	Size mm	mm	L mm	g	kg
118406M	6	120	190	59	10 / 40
118407M	7	120	190	77	10 / 40
118408M	8	200	300	306	10 / 60
118409M	9	200	300	306	10 / 60
118410M	10	200	300	317	10 / 60
118411M	11	200	300	323	10 / 60
118412M	12	200	300	326	10 / 60
118413M	13	200	300	333	10 / 60
118414M	14	200	300	344	10 / 60
118417M	17	250	300	599	6 / 36

T-type Standard Socket Wrench

1185M

- T-shaped standard socket wrench
- Chrome vanadium alloy steel
- DIN 475




KT NO.	Size mm	mm	L mm	g	kg
118508M	8	200	250	186	10 / 100
118509M	9	200	250	230	10 / 100
118510M	10	200	250	230	10 / 100
118511M	11	200	250	234	10 / 100
118512M	12	250	250	390	10 / 60

KT NO.	Size mm	mm	L mm	g	kg
118513M	13	250	300	425	10 / 60
118514M	14	250	300	429	10 / 60
118517M	17	300	360	710	6 / 36
118519M	19	300	360	727	6 / 36

T-type Spark Plug Socket

1563


- T-type 25° universal spark plug socket (rubber)
- Chrome vanadium alloy steel



KT NO.	Size mm	mm	L mm	g	kg
15631612	16	200	300	363	10 / 40
15631615	16	200	385	400	10 / 40
15631618	16	200	460	450	10 / 40
15631818	18	200	460	450	10 / 40
15632112	21	200	300	388	10 / 40
15632115	21	200	385	438	10 / 40
15632118	21	200	460	488	10 / 40

1566

- T-type 25° universal spark plug socket with magnet
- Chrome vanadium alloy steel



KT NO.	Size mm	mm	L mm	g	kg
15661615	16	200	385	420	10 / 40
15661618	16	200	460	460	10 / 40
15661818	18	200	460	450	10 / 40
15662115	21	200	385	460	10 / 40