

Insulated Screwdriver

KT No. & D1



- Shank material - SNM - V alloy steel
- Grip material - PP + TPR
- Finishing - chrome plated with black tip

1471



- Phillips head, round shank
- IEC 60900:2012

KT NO.	No.	mm		mm	g	mm	mm
		mm	inch				
14710003	PH0	75	3	3.0	37	12 / 144	
14710104	PH1	100	4	4.5	54	12 / 216	
14710204	PH2	100	4	6.0	77	12 / 144	
14710306	PH3	150	6	8.0	135	12 / 144	



147E



- Terminal Block Screwdriver
- Phillips / Slotted hand, round shank
- IEC 60900:2012



KT NO.	No.	mm		mm	g	mm	mm
		mm	inch				
147E0104	SL/PH1	100	4	4.5	61	12 / 216	
147E0204	SL/PH2	100	4	6.0	85	12 / 144	



1472



- Slotted head, round shank
- IEC 60900:2012

KT NO.	mm		mm		mm	g	mm	mm
	mm	inch	mm	inch				
14722503	2.5	-	0.4	75	3	2.5	35	12 / 144
14720303	3	1/8	0.5	75	3	3.0	38	12 / 144
14720404	4	3/16	0.8	100	4	4.0	44	12 / 96
14723504	3.5	1/8	0.6	100	4	3.5	54	12 / 144
14725505	5.5	7/32	1	125	5	5.5	72	12 / 144
14726506	6.5	1/4	1.2	150	6	6.5	87	12 / 144
14720807	8	5/16	1.2	175	7	8.0	143	12 / 144



1474



- Square head, round shank
- IEC 60900:2012

KT NO.	Size	mm		mm	g	mm	mm
		mm	inch				
14740105	RB1	125	5	5.5	72	12 / 144	
14740206	RB2	150	6	6.5	87	12 / 144	



1478



- Pozidriv head, round shank
- IEC 60900:2012

KT NO.	Size	mm		mm	g	mm	mm
		mm	inch				
14780003	PZ0	75	3	3.0	37	12 / 144	
14780104	PZ1	100	4	4.5	54	12 / 96	
14780204	PZ2	100	4	6.0	77	12 / 144	
14780306	PZ3	150	6	8.0	135	12 / 144	

