

# Composite Impact Wrench



## 33481

- One-handed F / R control
- 4-speed power setting, full speed in reverse
- TPR ergonomic handle material reduces vibration



lightweight  
**20% - 48%**

## 33681



33481



33681

KT NO.	Square drive		Type Std/Long anvil	Std. bolt size		Free speed R.P.M	Max. torque		Overall length		Air inlet	Air hose ID	Air pressure		Avg. air consumption	Sound DBA	Vib M/S2	Net weight			
	inch	mm		inch	mm		ft-lb	N-m	inch	mm			bar	psi				L/min	CFM		kgs
33481-095	1/2"	12.70	Std.anvil	1"	M24	8000	950	1288	7-3/4"	197	1/4"BSPT	3/8"	6.2	90	190	6.7	96.00	8.10	2.25	4.96	1 / 8
33481-096	1/2"	12.70	Std.anvil	1"	M24	8000	950	1288	7-3/4"	197	1/4"NPT	3/8"	6.2	90	190	6.7	96.00	8.10	2.25	4.96	1 / 8
33681-100	3/4"	19.05	Std.anvil	1-3/16"	M30	8000	1100	1491	8-3/8"	211	1/4"BSPT	3/8"	6.2	90	190	6.7	96.00	8.98	2.35	5.20	1 / 8
33681-101	3/4"	19.05	Std.anvil	1-3/16"	M30	8000	1100	1491	8-3/8"	211	1/4"NPT	3/8"	6.2	90	190	6.7	96.00	8.98	2.35	5.20	1 / 8

## 33631 / 33632

- Nickel chrome molybdenum square drive
- Variable speed trigger
- Muffled on handle exhaust



KT NO.	Square drive		Type Std/Long anvil	Std. Bolt Size		Free Speed R.P.M	Max. Torque		Overall Length		Air inlet	Air Hose ID	Air Pressure		Avg. Air Consumption	Sound DBA	Vib M/S2	Net Weight			
	inch	mm		inch	mm		ft-lb	N-m	inch	mm			bar	psi				L/min	CFM		kgs
33631-110	3/4"	19.05	Std. anvil	1-3/16"	M30	5500	1100	1491	8-43/64"	220	3/8"BSPT	1/2"	6.2	90	269	9.5	98.35	5.31	5.60	12.35	1 / 4
33631-111	3/4"	19.05	Std. anvil	1-3/16"	M30	5500	1100	1491	8-43/64"	220	3/8"NPT	1/2"	6.2	90	269	9.5	98.35	5.31	5.60	12.35	1 / 4
33632-110	3/4"	19.05	Long anvil	1-3/16"	M30	5500	1100	1491	14-55/64"	377	3/8"BSPT	1/2"	6.2	90	269	9.5	97.20	7.90	6.04	13.32	1 / 4
33632-111	3/4"	19.05	Long anvil	1-3/16"	M30	5500	1100	1491	14-55/64"	377	3/8"NPT	1/2"	6.2	90	269	9.5	97.20	7.90	6.04	13.32	1 / 4