

# Air Hydraulic Riveter



**33J1**

- Professional riveting, suitable for continuous operation with rivets made of steel, stainless steel, aluminium
- With sturdy metal housing
- Tractive power: 11922 N-f / 18532 N-f


KT NO.	Traction Power		stroke length		Capacity		Air Inlet	Air Pressure		Air Consumption		Sound	Vib	Net Weight		
	lb-f	N-f	inch	mm	AL. & Steel (inch/mm)	Stainless (inch/mm)	inch	bar	psi	L/min	cfm	DBA	M/S2	kgs	lbs	
33J11-100	2680	11922	9/16"	14	3/16"(4.8)	5/32"(4)	1/4" BSPT/NPT	6.2	90	123	3.5	80.00	1.21	1.50	3.30	1 / 10
33J12-100	4166	18532	3/4"	19	1/4"(6.4)	7/32"(5.6)	1/4" BSPT/NPT	6.2	90	148	4.2	80.00	1.21	2.00	4.30	1 / 6

# Air Blow Gun



**7990**

Copper Thread



- Ideal for cleaning
- Steel nozzle & nylon fiber handle
- Air pressure: 90 PSI recommended
- Air consumption: 1/4" hose-13cfm-350l/min , 3/8" hose-15cfm-430l/min
- Sound pressure: 85~90 dB
- Working pressure: 75~120 PSI/5.0~8.0 kgs
- Max pressure: 200 PSI/ 15 kgs

KT NO.	Air Inlet Inch	ℓ		L (mm)	g	kg
		Inch	mm			
79900-04	BSPT	4	100	245	200	20 / 100
79900-10	BSPT	10	250	420	240	25 / 50
79900-13	BSPT	13	330	475	260	25 / 50
79900-20	BSPT	20	500	650	300	25 / 50
79901-04	NPT	4	100	245	200	20 / 100
79901-10	NPT	10	250	420	240	25 / 50
79901-13	NPT	13	330	475	260	25 / 50
79901-20	NPT	20	500	650	300	25 / 50