

Super Duty Air Ratchet Wrench

37323

37423

- Ergonomically enhanced composite handle
- 360° exhaust rotation leads the air away from working area
- Unique head design: dust free and prevent deformation and triples the life of parts
- Dual pawl design provides higher torque



3/8" & 1/2"

37323
37423



KT NO.	Square drive inch mm	Type Std./Long anvil	Std. bolt size inch mm	Free speed R.P.M	Max. torque ft-lb N-m	Overall length inch mm	Air inlet inch	Air hose ID	Air pressure bar psi	Avg. air consumption L/min CFM	Sound DBA	Vib M/S2	Net weight kgs lbs
37323-080	3/8" 9.53	Std. anvil	3/8" M10	280	80 108	11" 279	1/4"BSPT	3/8"	6.2 90	113 4.0	94.00	2.52	1.25 2.76 1 / 12
37323-081	3/8" 9.53	Std. anvil	3/8" M10	280	80 108	11" 279	1/4"NPT	3/8"	6.2 90	113 4.0	94.00	2.52	1.25 2.76 1 / 12
37423-080	1/2" 12.70	Std. anvil	3/8" M10	280	80 108	11" 279	1/4"BSPT	3/8"	6.2 90	113 4.0	93.00	2.07	1.25 2.76 1 / 12
37423-081	1/2" 12.70	Std. anvil	3/8" M10	280	80 108	11" 279	1/4"NPT	3/8"	6.2 90	113 4.0	93.00	2.07	1.25 2.76 1 / 12

Air Ratchet Wrench

37235 / 37335 / 37435

- Working around tightly packed engines, machinery and equipment



1/4" & 3/8"

37235
37335



3/8"

37335



1/2"

37435



KT NO.	Square drive inch mm	Free Speed R.P.M	Max. Torque ft-lb N-m	Overall Length inch mm	Air inlet inch	Air Hose ID	Air Pressure bar psi	Avg. Air Consumption L/min CFM	Sound DBA	Vib M/S2	Net Weight kgs lbs
37235-030	1/4" 6.35	230	30 41	6-1/8" 155	1/4"BSPT	3/8"	6.2 90	71 2.5	92.00	10.50	0.49 1.08 1 / 20
37235-031	1/4" 6.35	230	30 41	6-1/8" 155	1/4"NPT	3/8"	6.2 90	71 2.5	92.00	10.50	0.49 1.08 1 / 20
37335-030	3/8" 9.53	230	30 41	6-1/8" 155	1/4"BSPT	3/8"	6.2 90	71 2.5	92.00	10.50	0.49 1.08 1 / 20
37435-075	1/2" 12.70	200	75 102	10-1/4" 260	1/4"BSPT	3/8"	6.2 90	113 4.0	92.00	10.50	1.20 2.64 1 / 20
37435-076	1/2" 12.70	200	75 102	10-1/4" 260	1/4"NPT	3/8"	6.2 90	113 4.0	92.00	10.50	1.20 2.64 1 / 20

Continuous Flow Air Grease Gun

9BV14

- Ideal for machine, automobile, farm and garden equipments, vehicles etc.
- 360° rotating handle



KT NO.	Air inlet (Inch)	Screw Thread	Air Source Range input (psi/bar) output (psi/bar)	Recommended Air Source input (psi/bar) output (psi/bar)	Capacity c.c. oz	Net Weight kg			
9BV1420	1/4"BSPT	M10 x 1.0P	60~150 psi (4.2~10.3 bar)	2400~6000 psi (165~413 bar)	90 psi (6.2 bar)	3600 psi (250 bar)	400 14	1.7	1 / 10

9BV1420 For Germany, South Africa, Egypt, etc.