

Impact Universal Joint Socket



KT No. & D1


4B55M

- Special design for confined spaces
- DIN 3121



Standard Length

4B55S 1/2"



KT NO.	mm/inch	D1 mm	D2 mm	ℓ mm	L mm	⚖️	📦
4B5510M	10	17.0	27.5	12	64	161	10 / 120
4B5511M	11	19.0	27.5	12	64	166	10 / 120
4B5512M	12	19.0	27.5	12	64	162	10 / 120
4B5513M	13	21.8	27.5	12	64	176	10 / 120
4B5514M	14	22.0	27.5	12	64	174	10 / 120
4B5515M	15	22.0	27.5	12	64	172	10 / 120
4B5516M	16	23.9	27.5	12	64	180	10 / 120
4B5517M	17	25.0	27.5	12	64	173	10 / 120
4B5518M	18	25.8	27.5	12	64	173	10 / 120
4B5519M	19	27.9	27.5	12	64	187	10 / 120
4B5521M	21	30.0	27.5	12	64	190	10 / 120
4B5522M	22	31.7	27.5	12	64	196	10 / 120
4B5524M	24	35.8	27.5	12	64	217	6 / 96
4B5512S	3/8	17.0	27.5	12	64	161	10 / 120
4B5514S	7/16	19.0	27.5	12	64	166	10 / 120
4B5516S	1/2	21.8	27.5	12	64	176	10 / 120
4B5518S	9/16	22.0	27.5	12	64	174	10 / 120
4B5520S	5/8	23.9	27.5	12	64	180	10 / 120
4B5522S	11/16	25.0	27.5	12	64	173	10 / 120
4B5524S	3/4	27.9	27.5	12	64	187	10 / 120
4B5526S	13/16	30.0	27.5	12	64	190	10 / 120
4B5528S	7/8	31.7	27.5	12	64	196	10 / 120
4B5530S	15/16	35.8	27.5	12	64	217	6 / 96


4A55M

- Special design for confined spaces
- DIN 3121



Deep Version

4A55S 1/2"



KT NO.	mm/inch	D1 mm	D2 mm	ℓ mm	L mm	⚖️	📦
4A5510M	10	17.0	27.5	19	91	195	10 / 80
4A5511M	11	19.0	27.5	19	91	207	10 / 80
4A5512M	12	19.0	27.5	19	91	202	10 / 80
4A5513M	13	21.8	27.5	19	91	207	10 / 80
4A5514M	14	22.0	27.5	19	91	217	10 / 80
4A5515M	15	22.0	27.5	19	91	228	10 / 80
4A5516M	16	23.9	27.5	19	91	234	10 / 80
4A5517M	17	26.0	27.5	19	91	256	6 / 60
4A5518M	18	26.0	27.5	19	91	248	6 / 60
4A5519M	19	27.9	27.5	19	91	259	6 / 60
4A5521M	21	30.0	27.5	19	91	272	6 / 60
4A5522M	22	31.7	27.5	23.5	91	278	6 / 60
4A5524M	24	35.8	27.5	24	91	309	6 / 60
4A5512S	3/8	17.0	27.5	19	91	195	10 / 80
4A5514S	7/16	19.0	27.5	19	91	207	10 / 80
4A5516S	1/2	21.8	27.5	19	91	207	10 / 80
4A5518S	9/16	22.0	27.5	19	91	217	10 / 80
4A5520S	5/8	23.9	27.5	19	91	234	10 / 80
4A5522S	11/16	26.0	27.5	19	91	256	6 / 60
4A5524S	3/4	27.9	27.5	19	91	259	6 / 60
4A5526S	13/16	30.0	27.5	19	91	273	6 / 60
4A5528S	7/8	31.7	27.5	23.5	91	278	6 / 60
4A5530S	15/16	35.8	27.5	24	91	309	6 / 60

Impact Bit Socket



- Air pressure must not exceed 90PSI (6.3bar)
- Adjust your air tool to its lowest torque output, should this torque level not be enough, increase it gradually

4055S 1/2"

- Hexagon head
- ANSI / ASME B107.2



KT NO.	inch	L mm	Max. torq Nm	⚖️	📦
405506S	3/16	60	36.0	66	10 / 180
405508S	1/4	60	93.6	74	10 / 180
405510S	5/16	60	144.0	77	10 / 180
405512S	3/8	60	264.0	80	10 / 180
405514S	7/16	60	420.0	84	10 / 180
405516S	1/2	60	518.0	88	10 / 180

4055M 1/2"

- Hexagon head
- DIN 3121



KT NO.	mm	L mm	Max. torq Nm	⚖️	📦
405504M	H4	60	20.8	72	10 / 180
405505M	H5	60	36.0	73	10 / 180
405506M	H6	60	62.4	74	10 / 180
405507M	H7	60	97.0	76	10 / 180
405508M	H8	60	144.0	78	10 / 180
405510M	H10	60	264.0	86	10 / 180
405512M	H12	60	480.0	99	10 / 180
405513M	H13	60	518.0	105	10 / 180
405514M	H14	60	650.0	110	10 / 180
405516M	H16	60	680.0	127	10 / 180
405517M	H17	60	715.0	180	10 / 80
405518M	H18	60	740.0	179	10 / 80
405519M	H19	60	786.0	199	10 / 80