Self Adjusting Clutch Alignment Setting Tool Set

9AK21

- Prevent damage to system and to keep adapter ring in right position
- Necessary for pre-tensioning self adjusting clutches before removal or installation, avoiding clutch deformation
- Prevents plate distortion
- Suitable for most SAC(Self Adjusting Clutches 3 and 4 holes) equipped on vehicles of FIAT GROUP, VW, AUDI, BMW, Mercedes-Benz, VOLVO, OPEL, RENAULT etc














Pulley Removing Wrench

9AL

• To lock the pulley during removing or assembling any type of pulley retaining bolt

KT NO.	Inch	mm	Ø mm	₹ a Ţ	\$/ \text{\ti}\}\\ \text{\te}\}}}}}}}}}}}}}}}}}}}}}}}}}}}}}} \endthend\text{\texi}}}}}}}}}}}}}}}}}}}} \endotinegeties }}}}}}}}}}}}}}}}} \endthend\text{
9AL11	14-3/8	365	40~140	540	12 / 36
9AL12	14-3/8	365	40~140	540	12 / 36











 Water pump pulley



Alternator pump pulley



 Oil filter removal & assembly

Universal Cooling Pump and Refiller Tool Set



DO NOT open the radiator cap on a hot engine

9AM01

- For testing leakage in radiator system
- Vacuum leakage testing and bubble-free refilling
- Special pick hooks to speed up replacement of pipes
- Quick-release coupling on each connections
- Rubber cones with functional diameter 17~40mm

KT NO.	Ty	/pe	ŢĸġŢ	&/ @
9AM010	Japan		3.40	1/5
9AM011	USA		3.40	1/5
9AM012	Europe		3.40	1/5







