

Nut Splitter Set

9TD062

- For removing stubborn nuts or over tightened bolts without damaging the bolt thread
- Suitable for nuts to a tensile class 6
- Do not overtighten to prevent damage to the threads under the nut

0.61 / 12 / 36

KT NO.	inch	Capacity mm	Hex (mm)
9TD602	1/2"~5/8"	12~16	14
9TD603	5/8"~7/8"	16~22	19



9TD064

Blow case size (mm) :
260 x 175 x 60 (0.096CUFT)

1.89 / 1 / 12

KT NO.	inch	Capacity mm	Hex (mm)
9TD601	5/16"~1/2"	9~12	12
9TD602	1/2"~5/8"	12~16	14
9TD603	5/8"~7/8"	16~22	19
9TD604	7/8"~1-1/8"	22~27	21



1/2" DR. Damaged Nuts Remover Socket & Set




Can't be used with pneumatic wrench

9TD403

1/2"

- Made of top quality SNCM alloy steel, provide good wear resistance and durability
- Ideal for the removal of rounded, damaged or corroded nuts, bolts, oil drain plugs, marine nuts and bolts, exhaust manifold nuts, pipe nozzle, and studs
- No need for pounding, chisels or torches



KT NO.	D1 mm	D2 mm	l mm	L mm		
9TD403-10M	16.0	22	8	50	76	10 / 180
9TD403-12M	18.0	22	11	50	78	10 / 180
9TD403-13M	20.0	22	11	50	85	10 / 180
9TD403-14M	21.0	22	11	50	88	10 / 180
9TD403-17M	24.5	25	15	50	113	10 / 180
9TD403-19M	27.0	27	15	50	124	8 / 80
9TD403-21M	29.4	27	16	50	139	8 / 80
9TD403-22M	30.5	27	17	50	140	8 / 80
9TD403-23M	31.8	27	17	50	119	8 / 80
9TD403-24M	33.0	27	17	50	143	8 / 80
9TD403-27M	36.0	27	18	50	145	8 / 80

9TD

1/2"



KT NO.	Contents		
9TD034MR	21, 22, 23, 27	0.58	4/36
9TD035MR	9TD403 12, 13, 14, 17, 19	0.52	
9TD036MR	10, 12, 13, 14, 17, 19	0.60	

