

Transmission Jack

9TY14

- Handle for easy adjustment
- Protection against overloading
- Pedal for hydraulic control
- Telescoping cylinder rams



9TY1421-05A-B



9TY1432-03A-B



9TY1433-05A-B



9TYZ1434-05A-B



KT NO.	Capacity (T)	Min height (mm)	Max height (mm)	N.W (kg)	G.W (kg)	CUFT	
9TY1421-05A-B	0.5	1140	1965	24	28.5	1.7	1/1
9TY1432-03A-B	0.3	1260	1735	33	35.5	1.98	1/1
9TY1433-05A-B	0.5	875	1855	76	85	5.85	1/1
9TYZ1434-05A-B	0.5	870	1795	50	56	3.38	1/1
9TYZ1421-05A-B	0.5	1180	1980	29.5	30.5	2.27	1/1
9TYZ1431-06A-B	0.6	1270	2075	36.5	37.5	2.93	1/1

With single pump 9TY1433-05A-B, 9TYZ1421-05A-B, 9TYZ1431-06A-B



9TYZ1421-05A-B




9TYZ1431-06A-B




9TY145

- With stronger steel base and nylon wheel



9TY145-004A-B



9TY145-006A-B



9TY145-008A-B



9TY145-015A-B



KT NO.	Capacity (T)	Min height (mm)	Max height (mm)	N.W (kg)	G.W (kg)	CUFT	
9TY145-004A-B	0.4	1240	2105	26	29	2.89	1/1
9TY145-006A-B	0.6	1135	1980	34	37	3.44	1/1
9TY145-008A-B	0.8	850	1840	46	49	3.13	1/1
9TY145-015A-B	1.5	1130	1915	55.5	59	3.45	1/1

Pneumatic Transmission Jack

9TY1436

KT NO.	Capacity (T)	Min height (mm)	Max height (mm)	N.W (kg)	G.W (kg)	CUFT	
9TY1436-10A-B	1	880	1915	81	90	5.85	1/1

With single pump 9TY1436-10A-B, 9TY1441-05A-B



9TY1436-10A-B

